

## *S645MF*anless (dual display + dual mini PCIe slots)

### SPECIFICATION

- **Core Logic**  
Intel GM45/ICH9M
- **Processor**  
Support Socket P, FSB 667/800/1066MHZ  
Intel Mobil CPU Celeron M 575, 585, T3100 ;  
Core2Duo P8400, P8600 CPU
- **Memory**  
Support SODIMM, DDR II 667/800MHz \*2  
Total memory size up to 8GB
- **Graphics**  
Integrated Intel Graphics Media Accelerator 4500MHD
- **Audio**  
High definition 6 channels audio CODEC
- **LAN**  
Built-in Intel 10/100/1000Mbps Ethernet controller
- **Fire Wire**  
Built-in OHCI 1394a 1.1 compliance; Support up to 400Mb transfer rate
- **Storage Devices**  
Support 2.5" SATA hard disk drive  
Support SATA Slim DVD-ROM Combo, DVD-RW drive
- **Hardware Monitor**  
CPU temperature, cooling fan speed, system voltage
- **Power Management**  
ACPI 3.0 compliance OS direct power management; Wake-on event
- **Switches and Connecting Ports**

<b>Front Panel:</b>	
1 x IEEE 1394 Fire wire port;	1 x USB 2.0 / 1.1 Port
1 x MIC Port;	1 x Ear Phone Jack
Power-on & Reset buttons;	Power and HDD LEDs
<b>Back Panel:</b>	
1 x VGA port;	1 x DVI-D port(optional)
1 x RS232(COM) port (optional second COM port)	
1 x Line-Out Phone Jack;	1 x RJ45 10/100/1000Mb Fast Ethernet
2 x PS/2 Ports for Keyboard & Mouse	
2 x USB 2.0 / 1.1 Ports;	1 x DC 12V Power-in Jack
<b>Internal:</b>	
1 x full size mini PCIe slot;	1 x half size mini PCIe slot
- **Dimension**  
160 x 250 x 58 mm
- **AC Adaptor**  
Universal 100~240V AC in/12V DC out Power adaptor
- **Accessories**  
Power Adaptor, Driver CD, User's Guide, CPU Heatsink, Screws Pack

