

## S645PG3

(Additional 3 GigaLAN + Express card slot + Mini PCIe slot)

### SPECIFICATION

- **Core Logic**  
Intel GM45/ICH9M
- **Processor**  
Support Socket P, FSB 667/800/1066MHZ  
Intel Mobil CPU Celeron M 575, 585, T3100 ;  
Core2Duo T7500, T9400, T9600, P8400 & P8600 CPU
- **Memory**  
Support SODIMM, DDR II 667/800MHz \*2; Memory size up to 8GB
- **Graphics**  
Integrated Intel Graphics Media Accelerator 4500MHD
- **Audio**  
High definition 6 channels audio CODEC
- **LAN**  
Built-in Four Intel 82573L 10/100/1000Mbps ethernet controllers
- **Fire Wire**  
Built-in OHCI 1394a 1.1 compliance; Support up to 400Mb transfer rate
- **Storage Devices**  
Support 2.5" SATA hard disk drive  
Support SATA Slim DVD-ROM Combo, DVD-RW drive
- **Hardware Monitor**  
CPU temperature, cooling fan speed, system voltage
- **Power Management**  
ACPI 3.0 compliance OS direct power management; Wake-on event
- **Switches and Connection**

#### Front Panel:

1 x IEEE 1394 Fire wire port; 1 x USB 2.0 / 1.1 Port  
1 x MIC Port;  
Power-on & Reset buttons; Power and HDD LED

#### Back Panel:

1 x VGA port  
1 x RS232(COM) port  
1 x Line-Out Phone Jack  
4 x RJ45 10/100/1000Mb Fast Ethernet  
1 x PCI-E Express card slot  
1 x Mini PCI-e/USB 2.0 mini card slot (\*Not support SATA or PATA SSD mini card\*)  
2 x PS/2 Ports for Keyboard & Mouse  
2 x USB 2.0 / 1.1 Ports;  
1 x DC 12V Power-in Jack

- **Dimension**  
146 x 250 x 42 mm
- **AC/DC Adaptor**  
Universal 100~240V AC in/12V DC out power adaptor
- **Accessories**  
Power Adaptor, Driver CD, User's Guide, CPU Cooler, Screws Pack

